



Rocá Release

Powdered Release with Integral Color

DESCRIPTION

Rocá Release is a blend of light fast pigments and a powdered waterproof chemical that inhibits concrete buildup on stamping tools. The usage of *Rocá Release* provides rich accents and a lush, antique look to the stamped concrete. With a wide array of colors available *Rocá Release* adds the contrast and mottled look that allows concrete surfaces to take on the appearance of natural products. Different colors of *Rocá Release* can be applied to the concrete surface to maximize creativity and aesthetic qualities.

USES

Rocá Release is a required part of *Rocá System Decorative Concrete*. It provides the quick, easy and clean release of stamping mats from the textured concrete. *Rocá Release* provides the barrier necessary for concrete not to be marred upon removal of stamping tools.

BENEFITS

- Bond-Breaker: Allows for quick, clean removal of stamping tools
- Color: Non-fading, permanent colored surfaces
- Cost Effective: Permanent color eliminates the need for painting
- Decorative: Creates accents, contrast and an antique look
- Consistent: Strict Quality Control testing and standards

STANDARDS

Rocá Release meets and exceeds the requirements of ASTM C-979, *Pigments for Integrally Colored Concrete*, in reference to color stability.

COVERAGE

Coverage requirements vary according to intended use, stamping tools used, set of concrete and desired color contrasts. *Rocá Release* should be applied at a minimum of 3 lbs per 100 ft².

PLACING

Adjacent concrete surfaces should be protected by plastic sheeting during application of the release. *Rocá Release* should be applied after the application of *Rocá Shake* and after final troweling is complete. *Rocá Release* should be broadcast in a thin, uniform manner covering the colored concrete surface. The release should not be broadcast from a point above knee level. Use a sidearm, casting motion. Best results are obtained by broadcasting with a masonry brush. Do not over apply *Rocá Release* as this will decrease texture and detail. Do not trowel the release into the surface. The stamping process should begin following application of the release. Remove excess *Rocá Release* only when the concrete surface has reached a hardened, final set. Early removal of release will mar the concrete and distort the applied patterns. Sweep the excess *Rocá Release* from the surface. Pressure wash to achieve the desired antique finish.

CURING & SEALING

After the concrete has been washed and allowed to dry completely, seal the surface with an approved *Rocá System* sealer such as *Rocá Seal* or *Rocá Shine*.

STORAGE

Normal cement storage and handling practices should be observed. Store material in an interior, cool, dry place. Shelf life is one year in original, unopened container.

LIMITATIONS

In addition to the limitations already mentioned, please note the following. *Rocá Release* should not be used as the primary concrete coloring agent. It is designed to be applied over freshly placed integrally colored concrete or *Rocá Shake* treated concrete. *Rocá Release* should not be mixed with water or polymers and used as a trowel or spray applied topping over hardened concrete. Fluosilicate type chemical hardeners should not be used on *Rocá Release* treated surfaces.

Packaging: 30 lb pail (13.6 kg), 36 pails per pallet



Rocá Release

Powdered Release with Integral Color

REGULATORY

Read and follow application information, precautions and Material Safety Data Information.

HMIS

Health 1, Fire 0, Reactivity 0

Prop 65

Warning! This product contains Crystalline Silica, a chemical known to the State of California to cause cancer or reproductive toxicity.

VOC Content

0 g/L

CAUTION

The use of gloves, goggles, dust masks and other protective clothing is recommended. If cement or sand particles get into eyes, rinse immediately with clean water and seek prompt medical attention.

TECHNICAL SERVICE

US MIX Co.

112 South Santa Fe Drive

Denver, CO 80223

Tel: 303.778.7227 Fax: 303.722.8426

Web Site: www.usspec.com

Color Statement

Rocá System color charts provide an approximate representation of applied materials. They are to be used as a guideline only. Multiple variations such as concrete mix design, concrete mix raw materials, job site conditions, weather and application, finishing and curing procedures will determine the final appearance. Due to these variables, US Mix can not guarantee the final appearance will be an exact match between site applications and the *Rocá System* color chart. US Mix strongly recommends job site samples provided by the same contractors that will perform the actual installation.

NOTICE OF LIMITED WARRANTY US MIX Co. (manufacturer) warrants to buyer that this product at the time and place of shipment is of good quality and conforms to the manufacturer's specifications in force on the date of manufacture when used in accordance with the instructions hereon. Manufacturer cannot warrant or guarantee any particular method of use, application or performance of the product under any particular condition. This limited warranty cannot be extended or amended by manufacturer's sales, people, distributors or representatives or by any sales information, specifications of anyone other than the manufacturer. Liability under this warranty is expressly limited to refund of the purchase price.

LIMITATION OF WARRANTIES AND LIABILITY Buyer assumes all risks associated with the use of this product. Manufacturer expressly disclaims all warranties expressed or implied including the warranties of merchantability and fitness for a particular purpose and all other warranties otherwise arising by operation of the law, course of dealing, custom, trade or otherwise. Buyer's exclusive remedy if this product is proven to be defective is limited to refund of purchase price by the manufacturer. Refund shall only be available if the buyer notifies manufacturer in writing within thirty days following discovery of any defect. Written notice shall be forwarded to US MIX Co. at 112 South Santa Fe Drive, Denver, Colorado 80223. No claim can be made twelve months after purchase of the product. Twelve months after the purchase manufacturer's duties with respect to the product and limited warranty shall be presumed to have been satisfied. Manufacturer in no event is liable for consequential damages.